



Item	manual searchlight	Brand	Imec
Item NO.	SL-2000	Material	casting aluminium
Input Voltage	220VAC 12VDC 24VDC	Power	150W(250W option)
Light Source	HID Xenon(third generation)	Lamp Luminous Flux(lm)	15000lm(25000lm option)
Temperature(CCT)	3000K,6000K,8000K	CRI(Ra>)	Ra>95
Beam angle	1°	Lamp dia	20cm
Current	AC 0.25A DC 1.5A-5.5A	Irradiation range	2000M
IP Rate	IP65	Color	gray
Lifespan	20000h	working temperature	normal type:-10°~+45°
Lamp Lifetime(Hour)	6000h		heating type:-30°~+45°
Net weight	3KG	dimension	24*20CM
Application	Homeland&Border Security,Prison Facilities&Prison Security,Maritime, Water &Electric Power,Aquaculture,Orchard,Farming,Terminal,Bridge		

## FEATURES

1. Searchlight made of aluminum, light weight, high strength
2. High strength tempered glass, high temperature resistance
3. Excellent convergence effect, the effective range of up to 2000m
4. HID light source, high brightness, up to 15000lm-25000lm
5. Strong light blindness: human can not look at the searchlight directly, strong light will make human temporary blindness
6. Reverse connection protection in DC voltage, searchlight will not burn even connected mistakenly.